

STATOIL LAZERWAY F 5W-30

PCMO

APPLICATIONS

LazerWay F 5W-30 is a modern, fully synthetic engine oil developed for the hardest demands in modern engines

F 5W-30 is recommended for use in all types of engines with demands according to the specifications below. It is needed for a big number of cars such as Ford, Citroën, Toyota etc

ADVANTAGES

LazerWay F 5W-30 secures good fuel economy by the decreased internal friction in the engine. The low viscosity secures the starting up at low temperatures

CHARACTERISTICS

The low viscosity of LazerWay F 5W-30 allows the oil pressure to increase fast also at low temperatures. This is a way to secure the lubrication of the most sensitive parts of the engine and minimizing the wear. The function of the hydraulic lifters will be safe and the noise eliminated at start. The synthetic base oil is very shear stable which is necessary for a long life. The oil is build to keep pistons and piston rings clean without coke. LazerWay F 5W-30 gives actively fuel saving.

In the official test according to CEC-L-54-A-96 is the fuel saving more than 2.5 %

TYPICAL INSPECTIONS

CHARACTERISTICS	METHODS	UNITS	
SAE-klass	-	-	5W-30
Densitet at 15 °C	ASTM D 4052	kg/m ³	859
Viskositet at 40 °C	ASTM D 445	mm ² /s	53
Viskositet at 100 °C	ASTM D 445	mm ² /s	9,4
CCS at -30 °C	ASTM D 5293	mPa.s	4900
Viscosity index	ASTM D 2270	-	162
Flampunkt COC	ASTM D 92	°C	230
HTHS	CEC L-36-A-9	mPas	3,0
Pour point	ASTM D 97	°C	-39

TESTS AND APPROVALS

API SJ/CF ACEA A1/B1 Ford WSS-M2C912-A1 / WSS-M2C913-A/B
Fuel Saving 2,5% (CEC-L-54-A-96).

HANDLING AND STORAGE

ERROR: Server error: Entry not found in index

The right to change product specifications is reserved.



Statoil Lubricants, 118 88 Stockholm.

Customer service tel 08-429 68 50, fax 08-429 68 51, email: smobest@statoil.com

2009-03-11

Friction Fighters™

